


600V N-Channel MOSFET

Features

- 7.5A,600v,RDS(on)=1.2Ω@VGS=10V
- Gate charge (Typical 30nC)
- High ruggedness
- Fast switching
- 100% Avalanche Tested
- Improved dv/dt capability



General Description

This Power MOSFET is produced using Truesemi's advanced planar stripe, DMOS technology. This latest technology has been especially designed to minimize on-state resistance, have a high rugged avalanche characteristics. These devices are well suited for high efficiency switch mode power supplies, active power factor correction, electronic lamp ballasts based on half bridge topology.

Absolute Maximum Ratings

| Symbol | Parameter | TSP8N60M | TSF8N60M | Units |
|----------|--|-----------|----------|-------|
| VDSS | Drain to Source Voltage | 600 | | V |
| ID | Continuous Drain Current(@TC = 25°C) | 7.5 | 7.5* | A |
| | Continuous Drain Current(@TC = 100°C) | 4.5 | 4.5* | A |
| IDM | Drain Current Pulsed (Note 1) | 30 | 30* | A |
| VGS | Gate to Source Voltage | | ±30 | V |
| EAS | Single Pulsed Avalanche Energy (Note 2) | 285 | | mJ |
| EAR | Repetitive Avalanche Energy (Note 1) | 15.5 | | mJ |
| dv/dt | Peak Diode Recovery dv/dt (Note 3) | 4.5 | | V/ns |
| PD | Total Power Dissipation(@TC = 25 °C) | 165 | 55 | W |
| | Derating Factor above 25 °C | 1.21 | 0.4 | W/°C |
| TSTG, TJ | Operating Junction Temperature & Storage Temperature | -55 ~ 150 | | °C |
| TL | Maximum Lead Temperature for soldering purpose, 1/8 from Case for 5 seconds. | 300 | | °C |

Thermal Characteristics

| Symbol | Parameter | TSP8N60M | TSF8N60M | Units |
|------------------|---|----------|----------|-------|
| R _{θJC} | Thermal Resistance, Junction-to-Case | 0.85 | 2.2 | °C/W |
| R _{θCS} | Thermal Resistance, Case-to-Sink Typ | 0.5 | -- | °C/W |
| R _{θJA} | Thermal Resistance, Junction-to-Ambient | 62.5 | 62.5 | °C/W |

TSP8N60M/TSF8N60M

Electrical Characteristics (TC = 25 °C unless otherwise noted)

| Symbol | Parameter | Test Conditions | Min | Typ | Max | Units |
|--------------------------------|---|--|-----|------|------|-------|
| Off Characteristics | | | | | | |
| BVdss | Drain-Source Breakdown Voltage | VGS = 0V, ID = 250uA | 600 | -- | -- | V |
| Δ BVdss / Δ TJ | Breakdown Voltage Temperature coefficient | ID = 250uA, referenced to 25 °C | -- | 0.57 | -- | V/°C |
| Idss | Drain-Source Leakage Current | VDS = 600V, VGS = 0V | -- | -- | 10 | uA |
| | | VDS = 480V, TC = 125 °C | -- | -- | 100 | uA |
| Igss | Gate-Source Leakage, Forward | VGS = 30V, VDS = 0V | -- | -- | 100 | nA |
| | Gate-source Leakage, Reverse | VGS = -30V, VDS = 0V | -- | -- | -100 | nA |
| On Characteristics | | | | | | |
| VGS(th) | Gate Threshold Voltage | VDS = VGS, ID = 250uA | 2.0 | -- | 4.0 | V |
| RDS(ON) | Static Drain-Source On-state Resistance | VGS = 10 V, ID = 3.75A | -- | 1.0 | 1.2 | Ω |
| Dynamic Characteristics | | | | | | |
| Ciss | Input Capacitance | VGS = 0 V, VDS = 25V, f = 1MHz | -- | 1255 | -- | pF |
| Coss | Output Capacitance | | -- | 115 | -- | |
| Crss | Reverse Transfer Capacitance | | -- | 14.2 | -- | |
| Dynamic Characteristics | | | | | | |
| td(on) | Turn-on Delay Time | VDD = 300V, ID = 7.5A, RG = 25Ω (Note 4, 5) | -- | 22 | -- | ns |
| tr | Rise Time | | -- | 90 | -- | |
| td(off) | Turn-off Delay Time | | -- | 76 | -- | |
| tf | Fall Time | | -- | 44 | -- | |
| Qg | Total Gate Charge | VDS = 480V, VGS = 10V, ID = 7.5A (Note 4, 5) | -- | 30 | -- | nC |
| Qgs | Gate-Source Charge | | -- | 5.2 | -- | |
| Qgd | Gate-Drain Charge(Miller Charge) | | -- | 16.3 | -- | |

Source-Drain Diode Ratings and Characteristics

| Symbol | Parameter | Test Conditions | Min. | Typ. | Max. | Unit. |
|--------|---------------------------|--------------------------------|------|------|------|-------|
| Is | Continuous Source Current | Integral Reverse p-n Junction | -- | -- | 7.5 | A |
| ISM | Pulsed Source Current | | -- | -- | 30 | |
| VSD | Diode Forward Voltage | Is=7.5A, VGS = 0V | -- | -- | 1.5 | V |
| trr | Reverse Recovery Time | Is=7.5A, VGS=0V,dIF/dt=100A/us | -- | 390 | -- | ns |
| Qrr | Reverse Recovery Charge | Is=7.5A, VGS=0V,dIF/dt=100A/us | -- | 3.3 | -- | uC |

NOTES

1. Repeatability rating : pulse width limited by junction temperature
2. L = 20mH, IAS = 7.5A, VDD = 50V, RG = 50Ω , Starting TJ = 25°C
3. Isd ≤ 7.5A, di/dt ≤ 200A/us, VD ≤ BVdss, Starting TJ = 25°C
4. Pulse Test : Pulse Width ≤ 300us, Duty Cycle ≤ 2%
5. Essentially independent of operating temperature



TSP8N60M/TSF8N60M

Fig 1. On-State Characteristics




Fig 2. Transfer Characteristics




Fig 3. On Resistance Variation vs. Drain Current and Gate Voltage




Fig 4. On State Current vs.




Fig 5. Capacitance Characteristics (Non-Repetitive)





Fig 6. Gate Charge Characteristics



TSP8N60M/TSF8N60M

Fig 7. Breakdown Voltage Variation vs. Junction Temperature




Fig 8. On-Resistance Variation vs. Junction Temperature




Fig 9-1 . Maximum Safe Operating Area for TSP8N60M




Fig 9-2 . Maximum Safe Operating Area for TSF8N60M





Fig 10. Maximum Drain Current vs. Case Temperature



TSP8N60M/TSF8N60M

Fig 11-1 . Transient Thermal Response Curve fo TSP8N60M





Fig 11-2 . Transient Thermal Response Curve for TSF8N60M



TSP8N60M/TSF8N60M

Fig. 12. Gate Charge Test Circuit & Waveforms




Fig 13. Switching Time Test Circuit & Waveforms





Fig 14. Unclamped Inductive Switching Test Circuit & Waveforms



TSP8N60M/TSF8N60M

Fig. 15. Peak Diode Recovery dv/dt Test Circuit & Waveforms

